















Stützringe/ Führungsringe

Profil	Typ	Standardwerkstoff	Druck (bar) ²	Temperatur (°C) ²	Gleitgeschw. (m/sec) ²
	BUR08	PU POM PTFE	-	-30 bis 105 -60 bis 100 -200 bis 260	-
	BUR09	PU POM PTFE	-	-30 bis 105 -60 bis 100 -200 bis 260	-
	BUR10	PU POM PTFE	-	-30 bis 105 -60 bis 100 -200 bis 260	-
	BUR11	PU POM PTFE	-	-30 bis 105 -60 bis 100 -200 bis 260	-
	BUR12	PU POM PTFE	-	-30 bis 105 -60 bis 100 -200 bis 260	-
	BUR13	PU POM PTFE	-	-30 bis 105 -60 bis 100 -200 bis 260	-
	BWR01	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR02	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR03	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR04	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR05	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR06	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR07	POM PGM	-	-60 bis 100 -200 bis 260	4
	BWR08	POM PGM	-	-60 bis 100 -200 bis 260	4