













Symmetrische Dichtungen

| Profil | Typ | Standardwerkstoff | Druck (bar) ² | Temperatur (°C) ² | Gleitgeschw. (m/sec) ² |
|---|----------|------------------------------|--------------------------|---|-----------------------------------|
|  | PRS06 | PU NBR | 400 160 | -30 bis 105 -25 bis 100 | 0,5 |
|  | PRS06A | PU NBR | 400 160 | -30 bis 105 -25 bis 100 | 0,5 |
|  | PRS06B | PU NBR | 400 160 | -30 bis 105 -25 bis 100 | 0,5 |
|  | PRS06C | PU NBR | 400 160 | -30 bis 105 -25 bis 100 | 0,5 |
|  | PRS06E | PU NBR | 400 160 | -30 bis 105 -25 bis 100 | 0,5 |
|  | PRS07 | PU/NBR | 400 | -25 bis 100 | 0,5 |
|  | PRS13-15 | PU/POM NBR/POM FKM/PGM | 500 250 250 | -30 bis 100 -25 bis 100 -20 bis 210 | 0,5 |
|  | PRS18 | PU/NBR | 400 | -25 bis 100 | 0,5 |
|  | PRS19B | PGM/1.4310 | 150 | -200 bis 260 | 2 |
|  | PRS19D | PGM/1.4310 | 150 | -200 bis 260 | 2 |
|  | PRS22 | PU/POM NBR/POM FKM/PGM | 400 160 160 | -30 bis 100 -25 bis 100 -20 bis 210 | 0,5 |
|  | PRS10-12 | PU/POM NBR/POM FKM/PGM | 500 250 250 | -30 bis 100 -25 bis 100 -20 bis 210 | 0,5 |