






















Kolbendichtungen

Profil	Typ	Standardwerkstoff	Druck (bar) ²	Temperatur (°C) ²	Gleitgeschw. (m/sec) ²
	PS01	PU NBR FKM	400 160 160	-30 bis 105 -25 bis 100 -20 bis 210	0,5
	PS01A	PU NBR FKM	25	-30 bis 105 -25 bis 100 -20 bis 210	1
	PS01B	PU NBR FKM	400 160 160	-30 bis 105 -25 bis 100 -20 bis 210	0,5
	PS02	PU/POM NBR/POM FKM/PGM	700 250 250	-30 bis 100 -25 bis 100 -20 bis 210	0,5
	PS02A	PU/POM NBR/POM FKM/PGM	700 250 250	-30 bis 100 -25 bis 100 -20 bis 210	0,5
	PS03	PU/NBR	400	-25 bis 100	0,5
	PS04	PU/NBR/POM	700	-25 bis 100	0,5
	PS05	NBR	25	-25 bis 100	1
	PS08	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	1 15
	PS08B	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	1 15
	PS08C	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	2
	PS08D	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	2
	PS08E	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	1 15
	PS08F	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	1 15
	PS81	PU/NBR PB, PK, PGM, PT, PEK/NBR PB, PK, PGM, PT, PEK/FKM	400 800 800	-25 bis 100 -25 bis 100 -20 bis 210	1 15
	PS09	PU/NBR/POM	400	-25 bis 100	0,5
	PS16	NBR	160	-25 bis 100	0,5
	PS17	PU/POM NBR/POM	400 250	-25 bis 100	0,5
	PS19	PGM / 1.4310	160	-200 bis 260	15
	PS23	PU/NBR/POM	400	-25 bis 100	0,5
	PS35	PU	400	-30 bis 105	0,5